



RGBW



Coastal protected



IP67 ideal for outdoor areas
and under water lighting

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Complete with wall fixings for easy installation

Can rotate and be angled to direct light

Separate white LED for permanent use

Compatible with a large range of controllers

Marine grade stainless steel for use in outdoor
and indoor environments

UL010RGBW COLOUR CHANGE

Colour change LED light (5W max.)

FEATURES

IP rating	IP67
CSP Switchable	RGBW
Tilttable (°)	360
Dimmable Option	Driver dependent
LED Lifetime	L50 50,000h
Colour Rendering Index	CRI>80
Rotation angle (°)	360

INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	700g
Construction Material	Stainless steel (316)
UK Bathroom Zone	I
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes

RGBW Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
UL010RGBW	1.1W	White (4000K)	40°	50	45	101
UL010RGBW	1W	Red	40°	38	38	75
UL010RGBW	1.1W	Green	40°	63	57	124
UL010RGBW	1.1W	Blue	40°	11	8	17

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	2x 1m CR575RGBW (outside diameter: 7.4mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F 5 CORE, 8MM OD

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	13
CCDRV75DMX	220-240V	Yes	Yes	2	13
CCDRV75RF	220-240V	Yes	Yes	2	13

ACCESSORIES

JB7	5-pole IP68 inline connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
CCRFCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately

BEAM ANGLE: 40°

