



## LED LYTE

Mini LED light

### FEATURES

|                        |                  |
|------------------------|------------------|
| IP rating              | IP30             |
| CSP Switchable         | Single CCT       |
| Tilttable (°)          | Fixed            |
| Dimmable Option        | Driver dependent |
| LED Lifetime           | L70 70,000h      |
| Colour Rendering Index | CRI>80           |
| Colour Consistency     | SDCM3            |
| Rotation angle (°)     | Fixed            |

### INSTALLATION INFORMATION

|                             |          |
|-----------------------------|----------|
| Input                       | 350mA DC |
| Maximum Ambient Temperature | 35°C     |
| Weight                      | 20g      |
| Inrush Current              | N/A      |
| Cut Out Size                | 26       |
| Construction Material       | Plastic  |
| UK Bathroom Zone            | N/A      |
| Electric Class (1, 2, 3)    | III      |
| Suitable for coastal areas  | No       |
| Mounting Options            | Wall     |



Quick and easy installation with plug and play connector



Coastal protected



IP30 perfect for interior applications

### WARRANTY

Warranty

7 years

### FEATURES & BENEFITS

Mini LED perfect for small room e.g. closets

Small & discreet

### PHOTOMETRICS @ 25°C

| Product code | Finish | W  | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|--------|----|--------|------|----|------|---------|--------|
| LED LYTE WW  | Chrome | 1W | 3000K  | 110° | 60 | 60   | 30      |        |
| LED LYTE 27  |        | 1W | 2700K  | 110° | 58 | 58   | 29      |        |
| LED LYTE RED | Chrome | 1W | Red    | 110° |    |      |         |        |

Energy rating is a reflection of the LED light source.

### WIRING INFORMATION

|                         |  |
|-------------------------|--|
| Cable / Flying Lead     | 1m (0.205mm <sup>2</sup> red & black PTFE) |
| Type of Wiring Required | Series                                     |

### LED DRIVER

| Driver    | Input    | SELV | Dimming | Bathroom Zone | Min | Max |
|-----------|----------|------|---------|---------------|-----|-----|
| DRV150700 | 220-240V | Yes  |         | N/A           |     |     |
| PSIP3509W | 220-240V | Yes  | No      | Outside zones | 1   | 8   |

### ACCESSORIES

|                    |                                     |                 |
|--------------------|-------------------------------------|-----------------|
| LED LYTE 1M EXT    | 1m Plug & Play extension lead       | Sold Separately |
| LED LYTE 6 WAY EXT | 6-way 1m Plug & Play extension lead | Sold Separately |

BEAM ANGLE: 110°

