






01604 495 151
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

Springbok Lite 27,000lm

200W High bay luminaire (Replaces 400W or 4x80W T5)

Features

IK rating	IK08
IP rating	IP65
Sensor Option	Microwave & Daylight
Dimmable Option	No
LED Lifetime	54,000h L70
CRI	80 Ra
SDCM	5 SDCM
Emergency Option	Yes

Installation information

Install Connector Type	Flying lead
Construction Material	ADC12 aluminium alloy tempered glass
Weight	2.20
Maximum Ambient Temperature	-20°C to +40°C
UK Building Regulations	Part P
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m	EM
HBL3N	Matt black RAL9017	200W	4000K	110°	27000	135	9664	530
HBL3NEM	Matt black RAL9017	200W	4000K	110°	27000	135	9664	530

Wiring information

Cable / Flying Lead	1.5m H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required	Parallel

Accessories

HBLMWS	High Bay Sbok Lite, Microwave sensor kit inc junction box and counterweight	Sold Separately
HBREM	High Bay Sbok Lite, Remote control for commissioning HBLMWS	Sold Separately
HBL3REFR	High Bay Sbok Lite, 200W 80-degree refractor	Sold Separately

Guarantee

4 years, 2 years on battery, 2 years on-site

Features & benefits

- High efficacy of 135lm/W
- Very light weight for easy installation
- Emergency option available
- Economical high bay for fast return on investment
- Easy to add microwave sensor kit includes junction box and counter weight
- On/off control with time delay and daylight switching (8-15 metres max)
- Suitable for jack chain, M10 drop rod or catenary wire suspension
- Pre-wired with 1.5M of H05RN-F cable for ease and speed of installation
- Replaceable driver for easy maintenance
- IK08 for robust impact protection

Beam angle: 110°

