

**4.6W** 4.6W at 700mA

 Coastal protected

**IP68** IP68 ideal for outdoor areas and under water lighting

## WARRANTY

Warranty 7 years

## FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution

Complete with wall fixings

Tilt & rotate for adjusting light

Antique brass finish, Marine grade stainless steel 316 & Black anodised aluminium

Long lifetime of 70,000hrs

PATENT: **GB2544975 EP3176502**



# UL030

High output universal LED light

## FEATURES

<b>IP rating</b>	IP68
<b>CSP Switchable</b>	Single CCT
<b>Tilttable (°)</b>	360
<b>Dimmable Option</b>	Driver dependent
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3
<b>Rotation angle (°)</b>	360

## INSTALLATION INFORMATION

<b>Input</b>	700mA DC
<b>Maximum Ambient Temperature</b>	35°C
<b>Weight</b>	680g
<b>Inrush Current</b>	N/A
<b>Construction Material</b>	Stainless steel (316), brass, anodised aluminium
<b>UK Bathroom Zone</b>	0
<b>SELV</b>	N/A
<b>Electric Class (1, 2, 3)</b>	III
<b>Earth Leakage</b>	N/A
<b>Suitable for coastal areas</b>	Yes

## Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
UL030DNBX40	Stainless steel	12°	4.6W	4000K	490	70	7975	
UL030DNBX27	Stainless steel	12°	4.6W	2700K	470	67	7649	
UL030DWBX30	Stainless steel	40°	4.6W	3000K	480	69	1029	
UL030DWBX40	Stainless steel	40°	4.6W	4000K	490	70	1050	
UL030ANAX30	Brass	12°	4.6W	3000K	480	69	7812	
UL030ANAX27	Brass	12°	4.6W	2700K	470	67	7649	
UL030AWAX30	Brass	40°	4.6W	3000K	480	69	1029	
UL030AWAX27	Brass	40°	4.6W	2700K	470	67	1007	
UL030BWBX30	Black anodised aluminium	40°	4.6W	3000K	480	69	1029	

Energy rating is a reflection of the LED light source.

## WIRING INFORMATION



<b>Cable / Flying Lead</b>	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Series

## LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP70018W	220-240V	Yes	No	0	1	3
PSDIM700	220-240V		Yes (1-10V)	0	1	11

## ACCESSORIES

<b>JB2 / JB4</b>	Waterproof junction box / Gel filled waterproof connector	Sold Separately
<b>WCR 275 BLACK</b>	2-core rubber cable	Sold Separately



<b>PLD UNI-DRIVE 700MA</b>	700mA Driver	Sold Separately
<b>PLD UNI-DRIVE 700MA</b>	IP65 700mA 2W - 18W Driver	Sold Separately



**COLLINGWOOD**  
LIGHTING

## LIGHTING INNOVATION

This versatile, swivel-mounted universal light offers endless possibilities and ensures that any corner of a landscape can be lit, whether that's a pond, tree or anything in-between. With a 360° stainless-steel bracket, 12° beam angle, IP68 water-resistance rating and bright 4.6W LED light output equivalent to a 35W halogen, it throws light into even the darkest and wettest environments.