



SALVUS EMERGENCY EXIT BLADE

50lm, emergency exit blade, 30m viewing distance

FEATURES

IP rating	IP20
IK rating	IK08
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80
Maintained / Non-Maintained	Maintained

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	45°C
Weight	0.9Kg
Inrush Current	10.3A 100ms
Construction Material	Lens PC housing PC
Electric Class (1, 2, 3)	II
Battery	LiFePO4
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Ceiling, wall & suspended
Viewing distance	30

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm
EMBL30M	White	Manual-test	4.0W	6500K	120°	50
EMBL30S	White	Self-test	4.0W	6500K	120°	50

WIRING INFORMATION

Cable / Flying Lead	Screwless terminals, up to 0.75mm ²
Type of Wiring Required	Parallel

ACCESSORIES

EMBLUP	Pictogram Arrow UP.	Sold Separately
EMBLDO	Pictogram Arrow DOWN.	Sold Separately
EMBLRI	Pictogram Arrow RIGHT.	Sold Separately
EMBLLE	Pictogram Arrow LEFT.	Sold Separately
EMBLSK	Suspension Kit (2x 1m cable + fixings)	Sold Separately



LiFePO4 battery available



Self-test or Manual test available



Auxiliary floor illumination to light areas under fitting

WARRANTY

Warranty

3 years

FEATURES & BENEFITS

Maintained, so it can be turned on/off when the mains is on

Has three M20 entry knock-outs (one on each side and one in the bottom), and rear BESA box fixing points

Housing is rugged and made of polycarbonate

30m viewing distance allowing it to be assembled in different room dimensions

Complying with ISO 3864-1, and proud members of the ICEL