

Arial Pro

LED CCT Downlight

Arial Pro 12/16/18/20W IP65 LED CCT Downlight

Part Code: 10955

The Arial Pro LED Downlight is a sleek looking luminaire designed to replace cumbersome CFL fittings.

- Switchable colour temperature 3000/4000/6000K
- Ideal for home and office environments
- IP65
- Tool Free - Plug & Play
- The maximum wattage stated is the upper limit that the product should be set to, based on the specified life hours and warranty



Anti Glare
Design



50,000
Life Hours



7 Year
Guarantee



IP44 & IP65
Options Available





Product Category	Fittings / Downlights
Application	LED Downlights
Product Warranty	7 Years (2 Years On Site)
EAN	5013588109558
Commodity Code	9405423100
Country of Origin	CN

Technical Specification

Wattage (W)	12/16/18/20
Volts (V)	220/240
Colour Temperature (K)	3000/4000/6000
Lumen Output (lm)	12W = 1567 (3000K) / 1731 (4000K) / 1551 (6000K) - 16W = 2090 (3000K) / 2308 (4000K) / 2068 (6000K) - 18W = 2351 (3000K) / 2597 (4000K) / 2327 (6000K) - 20W = 2612 (3000K) / 2885 (4000K) / 2585 (6000K)
Lumens per Watt (lm/W)	129-144
CRI (ra)	85
Frequency (Hz)	50/60
LED Drive Current	500mA
Energy Consumption (kWh/1000h)	20
Life Hours	50000
Switching Cycles	25000
IP Rating	IP65
Operating Temperature	-5°C - +35°C
Lumen Maintenance Ratio	80

Packaging Information

Minimum Order Quantity	1
Height (mm)	117
Diameter (mm)	240
Individual Product Weight (kg)	0.56
Single Box Weight (kg)	0.75
Single Box Height (mm)	143
Single Box Width (mm)	250
Single Box Depth (mm)	250
Single Box Volume	0.00894
Outer Box Qty	12
Outer Box Barcode	1095500000012
Outer Box Weight (kg)	10.5
Outer Box Height (mm)	475
Outer Box Width (mm)	515
Outer Box Depth (mm)	515
Outer Box Volume	0.12598
UNSPSC Code	39111515



ArialPRO

LED CCT Downlight

Additional Information

Beam Angle	90°
------------	-----